



DEVIlink™ RS

The DEVIlink™ RS (Room Sensor) is a battery operated device for measuring room temperature. It is only to be mounted directly on the wall.

When using the DEVIlink™ RS as heating regulation it must be installed together with a DEVIlink™ PR , DEVIlink™ HR or DEVIlink™ FT to secure the required comfort and convenience.

Be aware that all DEVIlink™ RS in the same room must have the same configuration.

Benefits:

- Heating regulation
- Wireless connected to DEVIlink™ CC
- Actually temperature view
- Adjustable
- Daily overview
- Weekly schedule
- Minimize energy consumption

Standard compliance:

- The DEVIlink™ RS is in compliance with EN 60730 and EN 300 220-2.

Certificates:



Type	Value
Battery	Alkaline 2 × AA, 1,5 V
Battery Lifetime	Up to 4-5 years
Backlight	Green LED
Ambient temperature	0° to +40°C
Battery monitoring	The sensor has a built-in monitoring circuit, which will detect low or critical battery level.
Transmission frequency	868,42 MHz
Transmission range in normal buildings	Up to 30 m
Transmission power	Max. 1 mW
IP class	21
Dimension (H/W/D)	81 mm × 66 mm x 21 mm

Types

Item no.	Product name	Type	EAN no.
19190004	DEVIlink™ RS	Room sensor-Wireless -Battery Supply	5703466174449

DEVIlink™ system units

Item no.	Product name	Type	EAN no.
140F1076	DEVIlink™ CC with PSU	Permanent Installation	5703466232460
140F1077	DEVIlink™ CC with NSU	Supply by Plug	5703466232477
088U0230	RU DEVIlink™ / Danfoss Link	Repeater Unit	5702420068244
088L1905	Danfoss Link™ FT	Floor Thermostat with ELKO frame	5703466174371
19190026	DEVIlink™ PR	Plug in Relay	5703466197271
19190027	DEVIlink™ HR	Hidden Relay	5703466197288

Do not install floor heating systems without a floor sensor when the heating element is installed on or beneath wooden surfaces and other surfaces sensitive to temperature!